

Technical Data Sheet

Removable White Polypropylene - 603

General Description: A white, bi-axially oriented' gloss polypropylene film, with a thermal transfer printing receptive top coating. The 603 has a transparent, dispersion based removable acrylic adhesive.

Uses & Features: Ideal for temporary marking. Removes with ease and leaves no residue on surface*. The product is suitable for promotional, temporary and short or long time applications. The face stock can be printed with thermal transfer printers. Due to good UV resistance the 603 can be used for indoor and out door application on most substrates.

* we advise to test on the substrate you use.

Recommended Ribbons: Nortec 103 or 104 Thermal Transfer Ribbons.

Thickness:

	gsm	Standard	um	Standard
Face	58	ISO536	59	ISO534
Adhesive*	12	14		
Liner	64	ISO536	57	ISO534
Total			130	-/+10

* A general purpose removable, acrylic based adhesive.

Adhesion:

Test	Results	Standard
Initial Tack	120N/m	FTM 9 glass
Peel Adhesion 90°	65N/m	FTM 2 st.

Service Temp. Range (long term): -40°C to 100°C (-40°F to 212°F) Service temp without visual or functional effect.

Application Temp. : Min. Application Temp: >0°C.

Shelf Life: 2 years when stored at 72°F (22°C)/50% RH.

Warranty: Nortec AMI recommends that a selected label type be thoroughly tested to insure it meets all end user requirements. Nortec AMI warrants only the purchaser that its products are free from defects in material and workmanship. Nortec AMI limits its obligation under this warranty and at its option to repair or replace the product. This warranty is in lieu of any other warranty, expressed or implied, including, but not limited to, any implied warranty of merchantability or fitness for a particular purpose. Nortec AMI is not liable for any damages, including lost profits, lost savings, or other incidental or consequential damages arising out of the use of or inability to use such product.

Form No.	Latest Revision	Created By	Date	Page
ND 7.5 - D	Rev1.12.17	Amir P.	26.12.2017	1 of 1